



A. Velcro tabs Detail

Install two 5" x 1" velcro tabs—the female/soft/loop part at the inside top of banner sleeve, 1" from both openings



Attach velcro with heavy-duty nylon or polyester thread using "box" stitching pattern, as illustrated above.

B. D-ring Detail



Note: Webbing to attach D-ring to banner should be sewn using heavy-duty nylon or polyester thread in the pattern shown above and reinforced with a brass grommet. Cotton thread is not acceptable.

Overview and timeline

All banners should be double-faced and lined with an opaque inner-liner.

After completing banner design, allow at least four weeks for production or rush charges may apply.

Banners must be delivered to UCD one week prior to installation.

Print area

Banner size minus 4" sleeve size (at top of banner).

Material

Nylon of similar fabric only. NO vinyl/PVC or Sunbrella allowed.

Printing

Acid-dye, dye sublimation or digital printing. Applique or pigment screen-printing for one-time, short-term installations ONLY.

2 D-Ring Tethers

Reinforced nylon web tab with a welded 1.5" D-ring at top and a welded 2" D-ring at bottom along the same edge. Placed 5" and 7'0" to center of ring from top of banner.

Approval

Any alterations to these specifications must be approved by University City District to ensure proper installation. Banners manufactured outside the parameters of these specifications without prior approval are in violation of the installation contract.

Contact

Mark Christman
Marketing and Communications Specialist
University City District
3940 Chestnut Street
Philadelphia, PA 19104

T: 215-243-0555 x229
E: mark@ucityphila.org



**university
city district**